

LIRA 240

INCASSI - RECESSED LIGHT FITTINGS



LED

17W - 4000K - **2452 lm** - 220-240V 50/60Hz
 17W - 3000K - **2372 lm** - 220-240V 50/60Hz
 17W - 4000K - **1660 lm** - 220-240V 50/60Hz
 17W - 3000K - **1590 lm** - 220-240V 50/60Hz
 3x1mm² H07RN-F (1mt)

RGB

9W - full color - 12V PWM
 4x0.5mm² H05RN-F (1mt)

E27

max 33W
 3x1mm² H07RN-F (1mt)
 Lampada non inclusa
 Lamp not included

MT

MT 35W/70W - G12
 MT 70W - Rx7s
 3x1mm² H07RN-F (1mt)
 Lampada non inclusa
 Lamp not included

Gruppo ottico basculabile di $\pm 15^\circ$ (solo MT)
 Morsettiera interna resinata
 Modalità di installazione a pavimento con
 utilizzo di controcassa circolare
 Diffusore in vetro piano temperato trasparente
 spessore 12mm (versione 17W, 9W, G12 e Rx7s)
 Diffusore in vetro piano temperato acidato
 spessore 12mm (versione 17W e E27)
 Controcassa in tecnopolimero rinforzato
 Corpo in pressofusione di alluminio anodizzato
 Cornice tonda in acciaio inox AISI 316L
 Viteria in acciaio inox A2

Adjustable $\pm 15^\circ$ (only MT version)
 Factory sealed termination chamber
 utilising resin to guarantee sealing
 Recessed box for floor installation
 Flat, transparent, tempered glass diffuser,
 12mm thickness (17W, 9W LED's, G12 and Rx7s
 versions)
 Flat, brushed, tempered glass diffuser,
 12mm thickness (17W LED's and E27 version)
 Black reinforced thermoplastic recessed box
 Anodised die-cast aluminium body
 AISI 316L stainless steel round ring
 A2 stainless steel screws

AISI 316L Inox 316L - Stainless steel

CE IP67 - IK08 **CARRABILE**
 Max Load
 2500Kg
 20Km/h



VETRO ACIDATO BRUSHED DIFFUSER

| Dimensioni Dimensions | Potenza Power | Colore Colour | Codice Code | |
|--------------------------|-------------------|------------------|----------------|---|
| Ø240x208mm | 17W 3000K 1590 lm | AISI 316L | 4240.191W | 1 |
| Ø240x208mm | 17W 4000K 1660 lm | AISI 316L | 4240.192W | 1 |
| Ø240x208mm | * max 33W - E27 | AISI 316L | 4240.101W | 1 |

Dimensione Dimension
 * (max Ø80 L137mm) Lampada non inclusa
 Lamp not included

VETRO TRASPARENTE TRANSPARENT DIFFUSER

| | | | | |
|------------|---------------------------|-----------|-----------|---|
| Ø240x208mm | 17W 4000K 15° 2452 lm | AISI 316L | 4240.482W | 1 |
| Ø240x208mm | 17W 4000K 45° 2452 lm | AISI 316L | 4240.582W | 1 |
| Ø240x208mm | 17W 4000K 60°x20° 2452 lm | AISI 316L | 4240.682W | 1 |
| Ø240x208mm | 17W 3000K 15° 2372 lm | AISI 316L | 4240.484W | 1 |
| Ø240x208mm | 17W 3000K 45° 2372 lm | AISI 316L | 4240.584W | 1 |
| Ø240x208mm | 17W 3000K 60°x20° 2372 lm | AISI 316L | 4240.684W | 1 |
| Ø240x208mm | 9W 6° RGB | AISI 316L | 4240.183W | 1 |
| Ø240x208mm | 9W 25° RGB | AISI 316L | 4240.283W | 1 |
| Ø240x208mm | 9W 45° RGB | AISI 316L | 4240.383W | 1 |

ATTACCO LAMPADA BASCULABILE ADJUSTABLE LAMP HOLDER

| | | | | |
|------------|----------------|-----------|-----------|---|
| Ø240x208mm | 35W MT G12 8° | AISI 316L | 4240.158W | 1 |
| Ø240x208mm | 35W MT G12 35° | AISI 316L | 4240.258W | 1 |
| Ø240x208mm | 35W MT G12 60° | AISI 316L | 4240.358W | 1 |
| Ø240x208mm | 70W MT G12 8° | AISI 316L | 4240.159W | 1 |
| Ø240x208mm | 70W MT G12 35° | AISI 316L | 4240.259W | 1 |
| Ø240x208mm | 70W MT G12 60° | AISI 316L | 4240.359W | 1 |
| Ø240x208mm | 70W MT Rx7s | AISI 316L | 4240.176W | 1 |

ACCESSORI - ACCESSORIES

| | | |
|--|-----------|---|
| Controcassa circolare Ø240x305mm I Recessed box Ø240x305mm | 7000.0006 | 1 |
| Morsettiera lineare IP68 - IP68 connector | CS093000 | 1 |
| Morsettiera derivazione a "T" IP68 "T"-3 way IP68 connector | CS093001 | 1 |
| Griglia antiabbagliamento solo G12 Anti glare grill only G12 version | 7000.0240 | 1 |


ACCESSORI OBBLIGATORI LED RGB COMPULSORY ACCESSORIES LED RGB

| | | | |
|---|---------|----------|---|
| Generatore DMX - DMX generator | Pag.153 | CS180011 | 1 |
| Controller DMX - DMX controller | Pag.153 | CS180008 | 1 |
| Kit cavo 4 poli - Kit 4 pole | Pag.153 | CS180018 | 1 |
| Morsettiera lineare IP68 - IP68 connector | Pag.153 | CS093002 | 1 |


| Generatore DMX 12VPWM DMX generator 12VPWM CS180011 | Controller DMX 12VPWM DMX controller 12VPWM CS180008 | Kit cavo connessione 4 poli Connection kit cable 4 poles CS180018 |
|---|--|---|
| • | max 5 | • |



A208
 BØ240
 CØ245
 D305



Controcassa circolare
 Circular recessed box



Morsettiera IP68
 IP68 connectors

