





MAIA

INCASSI - RECESSED LIGHT FITTINGS



LED














1.2W - 4000K - **80 lm** - 220-240V 50/60Hz
 1.2W - 3000K - **76 lm** - 220-240V 50/60Hz


-  Bianco - White
-  Grigio metallizzato - Metallic grey
-  Antracite - Anthracite



Scatola 503
Recessed box



| Dimensioni Dimensions | Potenza Power | Colore Colour | Codice Code |  |
|--------------------------|--|---|----------------|---|
| 85x130mm |  1.2W 4000K 80 lm |  B | 1008.182B | 1 |
| 85x130mm |  1.2W 3000K 76 lm |  B | 1008.184B | 1 |
| 85x130mm |  1.2W 4000K 80 lm |  M | 1008.182M | 1 |
| 85x130mm |  1.2W 3000K 76 lm |  M | 1008.184M | 1 |
| 85x130mm |  1.2W 4000K 80 lm |  S | 1008.182S | 1 |
| 85x130mm |  1.2W 3000K 76 lm |  S | 1008.184S | 1 |



Segnapasso ad incasso parete
 Verniciatura a polvere con pretattamento speciale per esterni
 Utilizzo su scatole incasso universali 3 moduli (503)
 Verniciatura a polvere con pretattamento speciale per esterni
 Scatola incasso universale in tecnopolimero
 Corpo in policarbonato trasparente
 Vano cablaggio e vano ottico IP65
 Maschera di copertura in policarbonato
 Viteria in acciaio inox A2

Wall recessed light fitting
 Polyester powder coating after a treatment specific for weathering resistance
 Polyester powder coating after a treatment specific for weathering resistance
 Thermplastic recessed box
 Transparent PC (polycarbonate) body IP65
 Polycarbonate and painted covering plate
 A2 stainless steel screws

