

SFERA 400 LED - IP44 A+

SFERE - GLOBES



LED

15W - 4000K - **2200 lm** - 220-240V 50/60Hz
 15W - 3000K - **2100 lm** - 220-240V 50/60Hz

- Bianco - White
- Trasparente - Transparent
- Semiverniciato - Semi-covered



Diffusore PMMA

Il diffusore sferico in Polimetilmetacrilato (PMMA) è dotato di eccezionale trasparenza ed è inalterabile alle radiazioni UV.

Disponibile in colore trasparente, bianco, o semiverniciato nero con verniciatura esterna nera e interna riflettente (versione dritta e rovesciata)

PMMA diffuser

The polymethylmethacrylate (PMMA) spherical diffuser has exceptional transparency and resistance to UV radiations.

It is available for uplight installation in clear or black semi-covered color and internally in reflective aluminium (uplight and downlight version)

Base IP44

Base in tecnopolimero rinforzato nero
 Bloccacavo autoregolante
 Utilizzo su palo e bracci Ø60mm
 Montaggio dritto
 Viteria in acciaio inox A2

Cablaggio


Cono cablaggio in tecnopolimero rinforzato per ricovero driver
 Aletta frangiluce in tecnopolimero rinforzato
 Cappello di copertura in tecnopolimero rinforzato
 Circuito circolare 50Led
 Alimentazione in corrente 500mA
 Emissione rotosimmetrica
 Driver elettronico incluso

IP44 base

Reinforced black thermoplastic base
 Self regulating cable block
 For use on poles and brackets Ø60mm
 Uplight mounting
 A2 stainless steel screws

Wiring

Reinforced thermoplastic covering cone for wiring and driver recovery
 Reinforced thermoplastic anti-glare louver
 Reinforced thermoplastic top cover
 Round LED circuit, 50 LEDs
 Power supplied at 500mA
 Symmetric throw
 Electronic driver included



CABLAGGIO DIRITTO
 UPLIGHT WIRING

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
Ø400mm Dritto - Uplight	■ 15W 4000K 2200 lm		1080.582B	1
Ø400mm Dritto - Uplight	■ 15W 4000K 2200 lm		1080.582T	1
Ø400mm Dritto - Uplight	■ 15W 4000K 2200 lm		1010.582T	1
Ø400mm Dritto - Uplight	■ 15W 3000K 2100 lm		1080.584B	1 new
Ø400mm Dritto - Uplight	■ 15W 3000K 2100 lm		1080.584T	1 new
Ø400mm Dritto - Uplight	■ 15W 3000K 2100 lm		1010.584T	1 new

