




FAST PLUS

CLICK AND LIGHT - THE TWIST REVOLUTION

LED

15W - 4000K - **1560 lm** - 220-240V 50/60Hz
 15W - 3000K - **1650 lm** - 220-240V 50/60Hz
 11.3W - 4000K - **1920 lm** - 220-240V 50/60Hz
 11.3W - 3000K - **1856 lm** - 220-240V 50/60Hz

 Bianco - White
 Grigio metallizzato - Metallic grey



Aggancio rapido tramite attacco universale brevettato Click a parete/soffitto in tecnopolimero rinforzato
 Possibilità di ordinare Click separatamente per una pre-installazione (Cod. 4000.1000), o incluso nel prodotto su versioni emergenza permanente ed emergenza permanente con sensore di presenza
 Cablaggio led o in emergenza permanente 3 ore, o con solo sensore di presenza o con emergenza permanente 3 ore e sensore di presenza
 Resa in emergenza 145Lm (3000K) 152Lm (4000K)
 Rilevatore di presenza con tre regolazioni: area rilevazione, temporizzazione, luminosità crepuscolare
 Diffusore in acrilico opale
 Corpo in ABS verniciato grigio metallizzato o bianco
 Cornice di decoro in ABS verniciato grigio metallizzato o bianco
 Verniciatura a polvere con pretattamento speciale per esterni
 Viteria in acciaio inox A2

Quick connection through the universal patented fastening system "Click" (reinforced thermoplastic fastening system)
 Click can be purchased separately in order to pre-set the installation (Cod. 4000.1000)
 It is included with the ceiling lamp in permanent emergency version or with permanent emergency and motion sensor
 Wiring in LED's, with 3 hours permanent emergency, with motion sensor or 3 hours permanent emergency and motion sensor
 Performance in emergency mode 145Lm (3000K) 152Lm (4000K)
 Motion sensor with 3 regulations: detection area, timing, twilight brightness
 Opal acrylic diffuser
 Painted thermoplastic body, metallic grey or white colours
 Painted thermoplastic frame, metallic grey or white colours
 Polyester powder coating after a treatment specific for weathering resistance
 A2 stainless steel screws







CE IP65







bianco - white

A+





LED - CLICK ESCLUSO LED - CLICK EXCLUDED

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
Ø300x95mm	15W 4000K 1560 lm		0263.182B	1
Ø300x95mm	15W 4000K 1560 lm		0263.182M	1
Ø300x95mm	15W 3000K 1650 lm		0263.184B	1
Ø300x95mm	15W 3000K 1650 lm		0263.184M	1





LED CON SENSORE DI PRESENZA - CLICK ESCLUSO LED WITH MOTION SENSOR - CLICK EXCLUDED


Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
Ø300x95mm	11.3W 4000K 1920 lm		0263.17AB	1
Ø300x95mm	11.3W 4000K 1920 lm		0263.17AM	1
Ø300x95mm	11.3W 3000K 1856 lm		0263.17BB	1
Ø300x95mm	11.3W 3000K 1856 lm		0263.17BM	1

LED CON EMERGENZA PERMANENTE 3 ORE - CLICK INCLUSO LED WITH 3-HOUR PERMANENT EMERGENCY - CLICK INCLUDED

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
Ø300x95mm	11.3W 4000K 1920 lm		0262.19AB	1
Ø300x95mm	11.3W 4000K 1920 lm		0262.19AM	1
Ø300x95mm	11.3W 3000K 1856 lm		0262.19ZB	1
Ø300x95mm	11.3W 3000K 1856 lm		0262.19ZM	1

LED CON EMERGENZA PERMANENTE 3 ORE E SENSORE - CLICK INCLUSO LED WITH 3-HOUR PERMANENT EMERGENCY MOTION SENSOR - CLICK INCLUDED

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
Ø300x95mm	11.3W 4000K 1920 lm		0262.19RB	1
Ø300x95mm	11.3W 4000K 1920 lm		0262.19RM	1
Ø300x95mm	11.3W 3000K 1856 lm		0262.19UB	1
Ø300x95mm	11.3W 3000K 1856 lm		0262.19UM	1



Attacco universale in tecnopolimero rinforzato
 Universal connection base in reinforced thermoplastic

Dimensioni Dimensions	Codice Code	
Ø155x46mm	4000.1000	10



grigio metallizzato - metallic grey