


FAST MAX PLUS

CLICK AND LIGHT - THE TWIST REVOLUTION

LED

30W - 4000K - **3120 lm** - 220-240V 50/60Hz
 30W - 3000K - **3300 lm** - 220-240V 50/60Hz
 21.7W - 4000K - **3410 lm** - 220-240V 50/60Hz
 21.7W - 3000K - **3300 lm** - 220-240V 50/60Hz

B Bianco - White
 Grigio metallizzato - Metallic grey



Aggancio rapido tramite attacco universale brevettato Click a parete/soffitto in tecnopolimero rinforzato
 Possibilità di ordinare Click separatamente per una pre-installazione (Cod. 4000.1000), o incluso nel prodotto su versioni emergenza permanente ed emergenza permanente con sensore di presenza
 Cablaggio led o in emergenza permanente 3 ore, o con solo sensore di presenza o con emergenza permanente 3 ore e sensore di presenza
 Resa in emergenza 145Lm (3000K) 152Lm (4000K)
 Rilevatore di presenza con tre regolazioni: area rilevazione, temporizzazione, luminosità crepuscolare
 Diffusore in acrilico opale
 Corpo in ABS verniciato grigio metallizzato o bianco
 Cornice di decoro in ABS verniciato grigio metallizzato o bianco
 Verniciatura a polvere con pretattamento speciale per esterni
 Viteria in acciaio inox A2

Quick connection through the universal patented fastening system "Click" (reinforced thermoplastic fastening system)
 Click can be purchased separately in order to pre-set the installation (Cod. 4000.1000)
 It is included with the ceiling lamp in permanent emergency version or with permanent emergency and motion sensor
 Wiring in LED's, with 3 hours permanent emergency, with motion sensor or 3 hours permanent emergency and motion sensor
 Performance in emergency mode 145Lm (3000K) 152Lm (4000K)
 Motion sensor with 3 regulations: detection area, timing, twilight brightness
 Opal acrylic diffuser
 Painted thermoplastic body, metallic grey or white colours
 Painted thermoplastic frame, metallic grey or white colours
 Polyester powder coating after a treatment specific for weathering resistance
 A2 stainless steel screws



LED - CLICK ESCLUSO LED - CLICK EXCLUDED

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
Ø400x105mm	30W 4000K 3120 lm	B	0263.282B	1
Ø400x105mm	30W 4000K 3120 lm		0263.282M	1
Ø400x105mm	30W 3000K 3300 lm	B	0263.284B	1
Ø400x105mm	30W 3000K 3300 lm		0263.284M	1

LED CON SENSORE DI PRESENZA - CLICK ESCLUSO LED WITH MOTION SENSOR - CLICK EXCLUDED

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
Ø400x105mm	21.7W 4000K 3410 lm	B	0263.27AB	1
Ø400x105mm	21.7W 4000K 3410 lm		0263.27AM	1
Ø400x105mm	21.7W 3000K 3300 lm	B	0263.27BB	1
Ø400x105mm	21.7W 3000K 3300 lm		0263.27BM	1

LED CON EMERGENZA PERMANENTE 3 ORE - CLICK INCLUSO LED WITH 3-HOUR PERMANENT EMERGENCY - CLICK INCLUDED

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
Ø400x105mm	21.7W 4000K 3410 lm	B	0262.29AB	1
Ø400x105mm	21.7W 4000K 3410 lm		0262.29AM	1
Ø400x105mm	21.7W 3000K 3300 lm	B	0262.29ZB	1
Ø400x105mm	21.7W 3000K 3300 lm		0262.29ZM	1


LED CON EMERGENZA PERMANENTE 3 ORE E SENSORE - CLICK INCLUSO LED WITH 3-HOUR PERMANENT EMERGENCY MOTION SENSOR - CLICK INCLUDED

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
Ø400x105mm	21.7W 4000K 3410 lm	B	0262.29RB	1
Ø400x105mm	21.7W 4000K 3410 lm		0262.29RM	1
Ø400x105mm	21.7W 3000K 3300 lm	B	0262.29UB	1
Ø400x105mm	21.7W 3000K 3300 lm		0262.29UM	1

grigio metallizzato - metallic grey



CLICK



Attacco universale in tecnopolimero rinforzato
 Universal connection base in reinforced thermoplastic

Dimensioni Dimensions	Codice Code	
Ø155x46mm	4000.1000	10



bianco - white