


SIMPLY PLUS

CLICK AND LIGHT - THE TWIST REVOLUTION

LED

10.8W - 4000K - **1459 lm** - 220-240V 50/60Hz
 10.8W - 3000K - **1400 lm** - 220-240V 50/60Hz

- Bianco - White
- Grigio metallizzato - Metallic grey



Aggancio rapido tramite attacco universale brevettato Click a parete/soffitto in tecnopolimero rinforzato
 Possibilità di ordinare Click separatamente per una pre-installazione (cod. 4000.1000), o incluso nel prodotto su versione emergenza permanente
 Cablaggio led o in emergenza permanente 3 ore, Resa in emergenza 125Lm (3000K) 131Lm (4000K)
 Diffusore in acrilico opale
 Corpo in ABS verniciato grigio metallizzato o bianco
 Cornice di decoro in ABS verniciato grigio metallizzato o bianco
 Verniciatura a polvere con pretattamento speciale per esterni
 Viteria in acciaio inox A2

Quick connection through the universal patented fastening system "Click" (reinforced thermoplastic fastening system)
 To be purchased separately in order to pre-set the installation (code 4000.1000), or along with the ceiling lamp in permanent emergency version LED's or in 3 hours permanent emergency
 Performance in emergency mode 125Lm (3000K) 131Lm (4000K)
 Opal acrylic diffuser
 Painted thermoplastic body, metallic grey or white colours
 Painted thermoplastic frame, metallic grey or white colours
 Polyester powder coating after a treatment specific for weathering resistance
 A2 stainless steel screws



grigio metallizzato - metallic grey



bianco - white



LED - CLICK ESCLUSO

LED - CLICK EXCLUDED

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
350X166x80mm	10.8W 4000K 1459 lm		0283.182B	1
350X166x80mm	10.8W 4000K 1459 lm		0283.182M	1
350X166x80mm	10.8W 3000K 1400 lm		0283.184B	1
350X166x80mm	10.8W 3000K 1400 lm		0283.184M	1

LED CON EMERGENZA PERMANENTE 3 ORE - CLICK INCLUSO

LED WITH 3-HOUR PERMANENT EMERGENCY - CLICK INCLUDED

Dimensioni Dimensions	Potenza Power	Colore Colour	Codice Code	
350X166x80mm	10.8W 4000K 1459 lm		0282.19AB	1
350X166x80mm	10.8W 4000K 1459 lm		0282.19AM	1
350X166x80mm	10.8W 3000K 1400 lm		0282.19ZB	1
350X166x80mm	10.8W 3000K 1400 lm		0282.19ZM	1

Ø155

CLICK



Attacco universale in tecnopolimero rinforzato
 Universal connection base in reinforced thermoplastic

Dimensioni Dimensions	Codice Code	
Ø155x46mm	4000.1000	10