



Zap

Technical details


- Luminaire available in E27 versions for pole top use on Ø60mm poles
- Silicone gaskets
- A2 stainless steel screws

Diffuser


- Non yellowing opal PMMA (acrylic) diffuser



Housing

- Reinforced thermoplastic housing in black granule, or metallic grey RAL 9006 painted



































A - Ø105
B - 300
Adapter Ø60

Power	Metallic grey RAL 9006	Black	
max 23W - E27	1310.101M	1310.101B	1

  Max lamp dimension allowed
(Ø70 L150mm)
Lamp not included





		 Teo	 Zap	 Chone
				 20W - E27 8W - Led
Ground installation		✓	✓	✓
Wall installation		--	--	--
Complying ECC standards		✓	✓	✓
Insulation class				
Voltage		220-240V 50/60Hz	220-240V 50/60Hz	220-240V 50/60Hz
Step MacAdam		--	--	3
Life time		--	--	L70/B50=54Kh-Tc 85°C
Colour temperature		--	--	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  3000K </div> <div style="text-align: center;">  4000K </div> </div>
Luminaire output		--	--	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">8W 793 lm</div> <div style="text-align: center;">8W 793 lm</div> </div>
Lamp holder		E27 - max 20W (lamp not included)	E27 - max 23W (lamp not included)	E27 - max 20W (lamp not included)
IP (Protection degree)		IP54	IP55	IP54
IK (Impact resistance)		IK06	IK04	IK08
Year warranty		✓	--	✓
Year warranty		--	✓	--
Photobiological risk		--	--	✓
Pre-wired with:		--	--	--
CRI		--	--	≥80
Connector IP68 CS093000 (linear) and CS093001 ("T"-3 ways) not included 		 The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm	 The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm	 The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm

Luna		Saturno	Versus					
✓		✓	✓					
--		--	✓					
✓		✓	✓					
☐		☐	☐					
220-240V 50/60Hz		220-240V 50/60Hz	220-240V 50/60Hz					
3		--	3					
L70/B50>60Kh-Tc 105°C		--	L70/B50>60Kh-Tc 105°C					
		--	Frontal light throw		Up-Down		Auxiliary light	
3000K	4000K	--						
9,4W 880 lm	9,4W 880 lm	--	13,4W 1000 lm	13,4W 1000 lm	13,7W Up-476 lm Down-408 lm	13,7W Up-476 lm Down-408 lm	2,2W 180 lm	2,2W 180 lm
E27 - max 10W (lamp not included)		E27 - max 10W (lamp not included)	E27 - max 10W (lamp not included)		--		--	
IP65		IP65	IP65					
IK03		IK03	IK04					
✓		✓	✓					
--		--	--					
✓		--	✓					
35cm cable H05RN-F 2x0,75mm ²		35cm cable H05RN-F 2x0,75mm ²	--					
≥80		--	≥80					
The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm		The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm	The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm					

Technical details

OUTDOOR RESIDENTIAL LUMINAIRE